# ClickShare Hub Core

Modular video conferencing room system for effortless hybrid meetings in Microsoft Teams Rooms



- **Wireless presentation: 4K content sharing with 1 Button**
- **Next-gen ClickShare Button with Wi-Fi 6E support and USB-C DisplayPort™**
- **Wireless BYOD for Microsoft Teams Rooms to run other videoconferencing platforms (Zoom, WebEx, Google Meet, etc.)**
- **Secure, cloud-managed, and built on the Microsoft Device Ecosystem platform (MDEP)**
- **Sustainable product with Barco Eco label A+**
- **Works as part of a room**

ClickShare Hub Core is a modular, wireless video conferencing system designed for effortless hybrid meetings.

The Hub Core works with the ClickShare Control Panel* and enables participants to start their meeting with a simple tap. Sharing 4K content is just as easy thanks to the next-gen ClickShare Button.

For IT managers and integrators, ClickShare Hub Core offers a customizable solution for all room types, and both ad hoc and scheduled meetings. Built on the Microsoft Device Ecosystem Platform (MDEP), it guarantees enterprise-grade security and compliance.

*The Control Panel, power cable and power cord are not included in this current package.

| Product specifications | CLICKSHARE HUB CORE |
|---|---|
| **General Specifications** | |
| Operating system | Android (MDEP) |
| Microsoft Teams Rooms license required | Yes |
| System requirements | For ClickShare App Minimum: Intel Core i3 or AMD Ryzen 5, 8GB RAM, Windows 10 20HS; Intel Core i3 or Apple Silicon M1, 8GB RAM, macOS 11 Big Sur<br>Recommended: Intel Core i5/Ultra 5 or AMD Ryzen 7, 8GB RAM, Windows 11 latest build; Apple Silicon M3, 8GB RAM, macOS latest build |
| Video outputs | HDMI: UW5K WUHD (5120*2160) @30Hz HDMI 2.0<br>eDP (Control Panel): HD (1280*800) @60Hz DP 1.4 |
| Video inputs | 4K UHD (3840*2160) @30Hz HDMI 2.0 |
| Audio output | USB-A 2.0/3.0 USB-C 2.0/3.0 HDMI 2.0 |
| ClickShare Buttons | 1 * ClickShare Button 5th Generation |
| ClickShare App | Desktop |
| Maximum sources simultaneously on screen | 1 |
| Noise Level | Maximum 25 dBA @ 30°C |
| Wireless transmission protocol | IEEE 802.11 a/b/g/n/ac/ax/be and IEEE 802.15.1 BT 5.3 |
| Reach | Max. 30m (100ft) between ClickShare Button and ClickShare Base Unit |
| Frequency band | 2.4GHZ, 5GHz and 6GHz DBS/HBS (DFS channels supported in select number of countries) |
| Connections | Back: 1x Ethernet LAN 1Gbit 1x USB-C Power delivery 3.1 EPR (for power adapter) 1x HDMI 2.0 output 1x USB-A 2.0/3.0 1x USB-C 2.0/3.0 1x USB-C 2.0/3.0 Device + USB-C DisplayPort™ output 1x USB-C 2.0 + USB-C DisplayPort™ output<br>Front: 1x USB-C 2.0/3.0 |
| Temperature range | Operating: 0°C + 40°C (+32°F to +104°F) Max 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to + 140°F) |
| Humidity | Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing |
| Anti-theft system | Kensington lock |
| Certifications | FCC/CE |
| Network connection | LAN |
| Management and reporting | Yes, XMS Cloud |
| Warranty | 3 years standard |
| Dimensions (HxWxD) | 37 * 180 * 180 (mm) |
| Power consumption | Operational: 140W (max) Standby: |
| Power supply | External USB-C charger 100W (PD3.0 SPR), 180W (PD3.1 EPR) |
| Weight | 720gr |
| Box content | ClickShare Hub Core Base Unit, 1 ClickShare Hub Button 5th Gen, Mounting disc, Safety manual, Quick setup guide |

**Last updated: 24 Jul 2026**

© 2026 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.